

CHART OF MALCOLM SCOPE MOUNTING REQUIREMENTS

RIFLE	17"/18" SHORT MALCOLM SCOPE		32" LONG MALCOLM SCOPE		ADDITIONAL THINGS NEEDED TO MOUNT LONG SCOPE
	FRONT MOUNT	REAR MOUNT	FRONT MOUNT	REAR MOUNT	
Winchester 1873-1876	ACC/900127				
Winchester 1885	ACC/900126				
1886 Models	All models need four holes drilled and tapped on barrel				
Marlin 94-95	ACC/900123				
Half Pint Sharps (Chiappa)	Old style distance between screw holes is ~0.825" (included w/scope) and new style distance is ~0.860" (900120 buy 2 non-drilled bases separately). Screws not supplied with scope.				
Sharps Scope Extension Tubes For Barrel Length	26-28" Barrel: 3" Extension 30" Barrel: (Included) 5" Extension 32" Barrel: 7" Extension 34" Barrel: 9" Extension				
Alternate Dovetail Block Sizes for Sharps	ACC/900113 0.5" BLOCK OR ACC/900116 0.625" BLOCK				
Pedersoli Full Size Sharps Rifles	ACC/900125		ACC/900100		Alternate size dovetail block if front/rear cuts on barrel are NOT 3/8", appropriate extension tube based on barrel length
Armi Sport/ Chiappa Full Size Sharps Rifles	ACC/900125		ACC/900100		Alternate size dovetail block if front/rear cuts on barrel are NOT 3/8", appropriate extension tube based on barrel length

** Standard long scope includes the following: the long scope with mounts (3/8" standard front ring, standard 3/8" dovetail block for rear mount), 5" sunshade for 30" barrel, heavy recoil tube-locking collar (TLC), and the sharps heavy duty base adaptor (SHDBA)

**Standard short scopes include the following: the short scope with rear and front mounts, bases included are drilled for 0.825 hole spacing

**18" scope has matte blue lens covers & long scope has brass lens covers (these are not interchangeable), 17" scope has no lens covers